

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

BEFORE THE PATENT EXAMINING OPERATION

ATTN'Y DOCKET NO.: ETS-TCA

APPLICATION OF: PETER BRITTINGHAM, MARY E. MORLEY, MARK K.
SINGLEY, MARK G. ZELMAN, KRISHNA N. JHA,
JAMES H. FIFE, ROBERT L. RARICH, IRVIN R.
KATZ, RANDY E. BENNETT

FOR: COMPUTER-BASED TEST-ITEM GENERATION AND
CLONING

PATENT SPECIFICATION

301256.1

EI469815916US

TABLE OF CONTENTS

BACKGROUND OF THE INVENTION	1
FIELD OF THE INVENTION	1
SUMMARY OF THE INVENTION	3
BRIEF DESCRIPTIONS OF THE DRAWINGS	6
DETAILED SUMMARY OF THE INVENTION	9
THE COMPUTER ENVIRONMENT	9
PROLOG IV	9
CREATING A NEW TEST ITEM	10
NEW FAMILY PROPERTIES DIALOG BOX	11
MULTIPLE CHOICE MODEL	13
CREATING A TEST ITEM MODEL	15
DEFINING VARIABLES BY INDICATING VALUES THE VARIABLES CAN TAKE ON	15
DEFINING VARIABLES DIRECTLY IN VARIABLES WINDOW	16
VARIABILIZING BY USING NAMING CONVENTION AND HIGHLIGHTING	16
VARIABLE NAMING CONVENTION FOR USE IN AUTO- DEFINING VARIABLES	16
IDENTIFYING ELEMENTS OF THE TEST ITEM TO BE VARIABILIZED	17
VARIABILIZING BY USING PRIOR UNFROZEN MODELS OR CHILDREN THEREOF	19
EDITING STRING VARIABLES	20
CREATING AND IMPORTING STRING VALUES	22
Using the "Add" Button	22
Using the "Export Strings" and "Import String" Buttons	23
EDITING INTEGER VARIABLES	24
SPECIFYING THE CONSTRAINTS	25
Operators	26
Variables	26
Functions	26
Constraining "IKey"	26

Exporting and Importing Constraints	27
Constraining the Distractors	27
Testing the Constraints	28
GENERATING TEST ITEM VARIANTS	29
WORKING WITH GENERATED VARIANTS	31
ACCEPTING VARIANTS	31
DEFERRING AND DISCARDING VARIANTS	31
CREATING NEW VARIANT MODELS FROM A GENERATED VARIANT	32
ACCEPTED VARIANTS AND NEW FAMILY MODELS	32
WORKING WITH MODELS AND ACCEPTED VARIANTS	33
EDITING THE PROFILE OF A VARIANT	34
The GRE Difficulty Portion of the Profile of a Variant Window	35
WORKING WITH FAMILY MEMBERS	36
Using a New Active Model to Generate Far Variants	36
Creating Still More Models	37
PRINT OPTIONS	38
GRE QUANTITATIVE COMPARISON ITEMS	39
GMAT DATA SUFFICIENCY ITEMS	40
FURTHER EXAMPLES OF ITEM MODELS	40
PROLOG SIMULTANEOUS CONSTRAINT SOLVER	41
HLP4lib.p4	41
PrlgExpr.l	41
PrlgExpr.y	41
hlp4API.h	42
TCA CONSTRAINT LANGUAGE	43
NOTATIONAL CONVENTION	44
TCA CONSTRAINT LANGUAGE IN DETAIL	44
BASIC ELEMENTS	46
Constants	46
Variables	46

Lists	47
Functions	47
Algebraic Expressions (referred to as: AlgExpr)	51
CONSTRAINT SPECIFICATION	53
Type Constraint Specification	53
Optimizable-Relation Specification	53
Precision Specification	55
Relational Constraints (RelExpr)	55
Ranges	56
Enumerated Range	57
if-then-else Constraint	58
if-then-elseif Constraint	59
Freeze Constraint	60
Primitive succeed and fail constraints	60
Combining Constraints	61
WRITING CONSTRAINTS IN TCA CONSTRAINT LANGUAGE	61
SOME TECHNIQUES TO SOLVE CONSTRAINTS IN TCA	63
Variable Type Specification.	63
Range specification.	64
Enumerated-Range Specification.	64
Efficient Solving	64
Representing lists and tables	65
Bidirectionality of functions and operators	66

Constraints are Solved in Order-independent Fashion	66
Constraints are Solved as a Whole	66
Variable Names are the Links to Bind Various Constraints	67
Use of Sets and Ranges	67
Logical Operators	68
Equality by Assigning Same Variable Name	68
VISUAL BASIC SOURCE CODE APPENDIX	69
PROLOG SOURCE CODE APPENDIX	73
CLAIMS	74
ABSTRACT	79

COMPUTER-BASED ITEM GENERATION

This application claims priority from U.S. Provisional Application Ser. No. 60/152,121, filed September 1, 1999, the disclosure of which is incorporated herein by reference. A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent disclosure, as it appears in the Patent and Trademark Office public patent files or records, but otherwise reserves all copyright rights whatsoever.

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

The present invention relates to computer-based technology in the generation of test items. In particular, to the semi-automated (i.e. test-developer assisted) generation of surface-level (near), medium-level, and deep (far) clones ("variants") of test items.

Applicants' assignee, Education Testing Service administers many different tests, including the following three tests. The Graduate Management Admission Test® (GMAT®) Program is used by

graduate business schools and measures general verbal, mathematical, and analytical writing skills that an individual has developed over a long period of time. The Graduate Record Examinations® (GRE®) Program provides tests that assist graduate schools and departments in graduate admissions activities. Tests offered include the General Test, which measures developed verbal, quantitative, and analytical abilities, and the Subject Tests, which measure achievement in 14 different fields of study. The SAT® Program consists of the SAT I: Reasoning Test and SAT II: Subject Tests. The SAT I is a three-hour test, primarily multiple-choice, that measures verbal and mathematical reasoning abilities. The SAT II: Subject Tests are one-hour, mostly multiple-choice, tests in specific subjects. These tests measure knowledge of particular subjects and the ability to apply that knowledge. The SAT® Program tests are used by colleges for admission or placement purposes.

These and other tests require a large number of test items. However, creating tests items is an expensive and time consuming process. Therefore, there is a need for a process and system for creating test items in a relatively cost effective and expeditious manner.

It is an object of the present invention to provide a process and system for the cost effective and expeditious creation of test items.

It is a further object of the present invention to provide a process and system for the cost effective and expeditious generation of test item variants from existing or newly created test items, wherein said test item variants can be used as test items.

SUMMARY OF THE INVENTION

A computerized method and system for creating test items by generating variants of a test item model, comprising the steps of creating a new test item model by identifying elements of an initial test item or a test item model to be variabilized, variabilizing the elements thereby creating test item variables, indicating values the variables can assume, specifying the constraints that define the relationships among the variables, and generating test item variants utilizing a simultaneous constraint solver.

The initial test item can be a pre-existing test item or test item model, a newly created test item or even a conceptual template in the mind of the test item creator. The generated test item variants are displayed to the test item creator. The

test item creator can store and forward acceptable test item variants for later use as test items. Test item models can be stored for later use in generating new test item variants.

In one preferred embodiment of the present invention, a frozen test item model can be extended to create its child which child model can be modified to generate its own test item variants. Moreover, item classification and tracking functions are provided. Test item creators can type in test items, edit them, import graphics, etc. Items that are created are compatible with test delivery software. Item management features allow the test developer to track the location and status of an item throughout its life cycle. In addition, items may be arranged in a searchable and browsable library in terms of whatever conceptual frameworks are used in the automatic generation and/or analysis of items. The text/graphics of these library items can be directly accessible by the item creation tools, i.e. the user is able to edit the text of a library item to create a new item.

One preferred embodiment of the present invention was written in Visual Basic, as well as the PROLOG IV programming language and provides an environment where the user can create a test item model or a family of test item models. For example, with this embodiment of the present invention, referred to as the

"Test Creation Assistant" or "TCA", the user may want to create a single model for a specific purpose, but could find out that it makes sense to have a family of models that have some sort of related theme and therefor TCA includes the notion of test model families.

Although preferred embodiments of the present invention are described below in detail, it is desired to emphasize that this is for the purpose of illustrating and describing the invention, and should not be considered as necessarily limiting the

invention, it being understood that many modifications can be made by those skilled in the art while still practicing the invention claimed herein.

BRIEF DESCRIPTIONS OF THE DRAWINGS

FIGS. 1 - 107 show the computer generated screen displays of one preferred embodiment of the present invention.

FIG. 1 shows the initial Test Creation Assistant window of this preferred embodiment and its associated work areas.

FIG. 2 shows the "File" menu options.

FIG. 3 shows the "New family properties" dialog box which appears by clicking on "New" in the "File" menu shown in FIG. 2.

FIG. 4 shows the "Save new family as" dialog box which appears by clicking on the "OK" button in the "New family properties" dialog box shown in FIG. 3.

FIG. 5 shows the result of the user entering "NEWMC" as the name of a family of test items in FIG. 4 and saving the choice.

FIG. 6 shows the TCA Standard Multiple Choice Model Word template of this preferred embodiment.

FIG. 7 shows the stem after the user has entered an initial test item.

FIGS. 8 and 9 show one way to identify elements of the test item to be variabalized using a preferred naming convention.

FIGS. 10-12 show a method for variabalizing and autodefining preidentified test item elements.

FIG. 13 shows the result of auto-defining the variables.

FIGS. 14 - 18 and 24 - 26 show how string variables may be edited in accordance with a preferred embodiment of the invention.

5 FIGS. 19 - 20 show how string variables may be exported to a file for later use in accordance with a preferred embodiment of the invention.

10 FIGS. 21 - 23 and 27 - 29 show how integer variables may be edited in accordance with a preferred embodiment of the invention.

15 FIGS. 30 - 44 show how the variable constraints may be specified in accordance with a preferred embodiment of the invention.

20 FIGS. 31 - 51 show how test item variants may be generated in accordance with a preferred embodiment of the invention.

 FIGS. 52 - 56 show how the user can work with generated variants in accordance with a preferred embodiment of the invention.

25 FIGS. 56 - 78 show how the user can work with models and accepted variants in accordance with a preferred embodiment of the invention.

 FIGS. 79 - 88 shows one way to print variants and the print outs generated by the system, after the user clicks on "Print

All" in Fig. 79, the print outs showing the variables and constraints, test item model, and test item model variants in accordance with a preferred embodiment of the invention.

FIGS. 89 - 91 show screen displays from Quantitative Comparison items in accordance with a preferred embodiment of the invention.

FIGS. 92 - 93 show screen displays from Data Sufficiency items in accordance with a preferred embodiment of the invention.

FIGS. 94 - 106 show screen displays for various item types in accordance with a preferred embodiment of the invention.

FIG. 107 show an overview of the computer architecture for one preferred embodiment of the present invention.

DETAILED SUMMARY OF THE INVENTION

THE COMPUTER ENVIRONMENT

DS 117
5 The computer system of the present invention was designed so that people could use it at home as well as on currently available desktops at work or notebooks. One preferred embodiment works with Microsoft® Windows 95, 98 or NT. This embodiment requires Microsoft® WORD 97, PROLOG IV and a Control Language Program called TCL 7.6, which is available on the
10 Internet at <http://www.scriptics.com>. See the Source Code Appendix for further details about this embodiment. The present invention is not limited to the foregoing operating systems, programming languages and/or software applications, etc. For example, an extensible markup language editor could be used in
15 place of Microsoft® WORD.

PROLOG IV

Prolog IV, is a compiled constraint programming language. The Prolog IV language allows the programmer to process a wide
20 variety of constraints describing relations over real and rational numbers, integers, booleans and lists. The Prolog IV constraint solving techniques are based on exact and approximation methods.

105 A 37 PROLOG IV is distributed by PrologIA, Parc Technologique de
Luminary - Case 919, 13288 Marseille cedex 09, France. Further
information about PROLOG IV can currently be found at
<http://prologianet.univ-mrs.fr>. PROLOG IV is a programming
5 environment.

CREATING A NEW TEST ITEM

In accordance with the preferred embodiment as exemplified
10 by the software application disclosed in the SOURCE CODE
APPENDICES, the user upon initializing the software application
is presented with the initial Test Creation Assistant window.

FIG. 1.

105 A 47 The initial window is subdivided into several work areas.
15 One important area is the Microsoft® Word area, which occupies
most of the left side of the initial window. Also important are
the three tabbed areas: "Family Overview"; "Model Workshop"; and
"Generate Variants" and the two pull down menus: "File" and
"Help". FIG. 1.

20 The Family Overview windows provide information regarding
Family members and Accepted variants and permits the user to Set
Attributes and Print a Family member. The Model Workshop tab
moves the user to areas for creating variabilized test items.

The Generate Variants tab permits the user to generate one or more test item variants. An item variant is a test item automatically generated from an item model, where the item model is comprised of constraints, stem, and key. In this tab, item variants can be displayed, saved or rejected.

Clicking on "File" menu heading in FIG. 1, opens the pull down menu shown on FIG. 2. The menu options are "New", "Open", "Import Locked Item", "Print Setup" and "Exit".

NEW FAMILY PROPERTIES DIALOG BOX

Clicking on "New" brings up the "New family properties" dialog box. FIG. 3. Using this dialog box the user can select the particular family properties for the new test item. Family properties refers to the major properties associated with a test item. In one preferred embodiment, it refers to the type of "Program" (e.g., GMAT®, GRE®, or SAT®), the "Item type", the "Variant proximity" and whether the test item is to be "generic" or "non-generic".

In the New family properties dialog box, using a drop-down menu, the user can select the "Program": GMAT®, GRE®, or SAT®. GRE has been selected. FIG. 3.

In the New family properties dialog box, the user can also select the "Item Type" or format of the question, in this embodiment: Multiple choice (MC), Quantitative comparison (QC),

or Data sufficiency (DS). All three options are shown in FIG. 89; while Multiple choice appears in FIG. 3.

The user can also select the "Variant proximity": the choices are: Near (variants that are easily recognizable as belonging to the same variant family by test developers and test takers, this selection is shown in FIG. 3); Medium (variants that are not easily recognizable as belonging to the same variant family by test developers and test takers); and Far (variants which are difficult to recognize as belonging to the same variant family). Once selected, the user may strive to ensure that generated variants are of the identified proximity.

Finally, the user has the choice of selecting either "Generic" items or "Non-generic" items. Pure items, i.e., test items in a mathematical setting, are Generic as long as they have no distinguishing surface features, such as an unusual figure or table. Real items, i.e., test items based on a real-life situation, are Generic only if the context is commonly used in the text. For example, common context for GMAT includes buying and selling questions, profit questions, stock questions, interest questions, etc. These would not be Generic items for GRE, since the GRE is not aimed at a business school population. Generic items for GRE would include simple rate-time-distance questions, percent questions, etc.

Clicking on the "OK" button in FIG. 3 brings up the "Save new family as" dialog box shown in FIG. 4. The user then enters the name of a family of test items, for example "NEWMC" and clicks on the "Save" action button, the file is saved as a "Model Doc Files (*\$R.doc) and the result is shown in FIG. 5.

At this point the Program (GRE), Family (NEWMC\$R.doc), Attributes (Single multiple choice or SMC; Non generic and Near), and the Active Model (NEWMC\$R.doc) are displayed in status bars at the bottom of the ETS Test Creation Assistant window. This information is displayed to the user across all three tabs: Family Overview (FIG. 5); Model Workshop (FIG. 13); and Generate Variables (FIG. 50).

MULTIPLE CHOICE MODEL.

DS A5 In the left part of the window in FIG. 5 appears the Microsoft Word document window with titles: "TCA Standard Multiple Choice Model", "reserved for variants", "stem", and "key". (Also present but not shown are the distractor titles and scratch pad, which can be seen in FIG. 6.) The first title will depend on the item type that the user chooses in the "New family properties" dialog box, see for example FIG. 3. The TCA Standard Multiple Choice Model Word template as printed out is shown in FIG. 6. When the user chooses Quantitative comparison, see FIG. 89, the result shown in FIG. 90 is the TCA Quantitative

Comparison Model (see also FIG. 91), if Data Sufficiency is chosen the result shown in FIG. 103 is the TCA Data Sufficiency Model (see also FIG. 105).

In the right part of the window in FIG. 5 the "Family Overview" tab is highlighted. In "Family members" appears an icon with a "Sun" and the name of the variant family, chosen in FIG. 4, "NEWMC", and an extension "\$R.doc". The "R" identifies the test item model as the root model, while the ".doc" identifies the file as a WORD document. The "Sun" icon indicates that the model is active, that is, an item model that has of yet not produce accepted variants and, therefore, is not blocked for future changes.

At the bottom of the "Family members" are two active buttons: "Extend" and "Remove". These buttons enable the user to extend or remove a variant family, respectively.

Creating an item begins with making entries in the "stem" section of the TCA Standard Multiple Choice Model. This is preferably done in the "Model Workshop" environment, but may be started in the "Family Overview" environment as shown in FIG. 7. As shown in FIG. 7, the user entered the following initial test item.

If John has 5 apples and Mary has 6 apples, how many apples do they have together?

CREATING A TEST ITEM MODEL

The present invention provides for the automatic generation
5 of test item variants. To do this the user builds a test item
model. Both the John and Mary initial test item above and an
existing model can form the basis for building a new test item
model. A test item model, whatever its size, consists of
"variables" and "constraints". A constraint is a statement
10 specifying the relationships among the variables. A variable, in
turn, indicates an item element that can take on more than one
value. Variables are defined by the user in terms of type
(integer, real, string, etc.) as well as the value range those
variables can take on. Therefore, to build a new model the user
15 needs to introduce some variables and define a set of constraints
for those variables-- the variabilizing process.

DEFINING VARIABLES BY INDICATING VALUES THE VARIABLES CAN TAKE ON

In accordance with one preferred embodiment of the present
20 invention, there are three ways of starting the variablizing
process: direct entry of information related to the term to be
variabilized, such as, name of variable, type, etc.; by pre-
defining variables in the stem using a naming convention so that
the system will automatically include the variable and its

associated information in the "Variables" window; or by starting with existing test item models or their child models.

DEFINING VARIABLES DIRECTLY IN VARIABLES WINDOW

5 The first method is to go over to the Model Workshop tab, and under the "Variables window" in the Model Workshop click on "Add", a "Create or Change Variable" dialog box will open, similar to that shown in FIG. 22, except that the "Variable Name" box is empty and the user must type the name in himself/herself
10 instead of having the system do it automatically as in the second method.

VARIABILIZING BY USING NAMING CONVENTION AND HIGHLIGHTING

15 The second method is to rename those elements of the initial test item when in the stem in accordance with the naming convention disclosed below, highlight the text typed in the stem section, right click and chose variablize, and the system will allow the user to automatically add all capitalized words which are highlighted.

VARIABLE NAMING CONVENTION FOR USE IN AUTO-DEFINING VARIABLES

20 When naming variables in the stem for use in auto-defining variables, one preferred embodiment of the present invention uses

the following conventions. Names of the variables are made up of letters and digits; however the first character must be a letter. A string variable begins with an "S"; an integer variable begins with an "I"; a real variable begins with an "R"; a fraction begins with an "F"; and an untyped variable begins with an "U".

A "String Variable" is a variable that does text substitutions, it does not involve mathematical operations. The system just searches and replaces one combination of letters, numbers, and/or symbols with another. For example, the text substitutions could

be substituting a male name from a list of male names. On the other hand, the text substitutions could be as complex as substituting a model (with all its variables) from a list of models, etc. "Untyped variables" are any variables representing a list, a boolean, or whose type is not known at test-item design time. These variables need not be defined unless they are referenced in the stem or in the distractors. Related information can be found in the TCA CONSTRAINT LANGUAGE section below.

IDENTIFYING ELEMENTS OF THE TEST ITEM TO BE VARIABILIZED

Using the naming conventions above, elements of the test item to be variabilized can be identified. The elements are identified by typing variable identifiers in place of the original test item element. An example of one such

identification is shown in FIG. 8 and FIG. 9. The user changed John to "SMaleName" and Mary to "SFemaleName". The "S" indicating that the variable is a string variable. The user replaced the numbers 5 and 6 with "INum1" and "INum2",
5 respectively. The "I" indicating that the variable is an integer. The user also replaced "apples" with "SItems", another string variable. So the stem portion has become:

"If SMaleName had INum1 SItems and SFemaleName had
INum2 SItems, how many SItems would they have
10 together?"

FIG. 9.

The user also changed the key from "Key" to "IKey" and all the distractors from "Distractor_" to "IDistractor_", because he/she is contemplating that all the solutions will be integers.

15 FIG. 9.

At this point, variables can be defined by highlighting the terms to be variabilized and then right clicking. FIG. 10. In the menu that appears, highlight and click "Variabilize". The result is shown in FIG. 11.

20 The "New variable detected" dialog box with words "Auto-define variable ...?" appears. The system will try to auto-define any sequence of letters or digits that begins with a capital letter. The system asks the user whether the first word which is

capitalized "If" should be auto-defined as a variable. The user should click on "No", which causes the system to address the next capitalized word "SMaleNames". FIG. 12. The result of clicking on "Yes" with respect to all words to be variabilized is to automatically classify the chosen terms in accordance with the naming convention. All chosen terms then appear in the "Variables" window as is shown in FIG. 13. Providing the user with additional information, not only do the names of the variables appear the "Variables" window, but also their characteristics. For example, string, integer, etc.

VARIABILIZING BY USING PRIOR UNFROZEN MODELS OR CHILDREN THEREOF

The third method is to chose an existing unfrozen model or child model and edit the existing variables and constraints in the Model Workshop. This is an important advantage of the preferred embodiment of the present invention, as it permits the reuse of prior test item models. If the model is frozen, it can still be used by extending the model and having the system create a "child" model of it; if the model is unfrozen, it can be used or, again, the system can create a "child" model of it. In either case, the "Variables" window, as well as other "constraint" windows, in the Model Workshop are populated with

variablized terms, ready for modifying through the editing process. See, FIG. 55 - FIG. 57, FIG. 71 - FIG. 77, and FIG 81.

EDITING STRING VARIABLES

5 At this point, all the selected variables appear in the "Variables" window. Next the variables must be constrained by assigning values or expressions to them. One way of doing this, is to select a particular variable by making a left mouse button click on the chosen variable, then right clicking, which brings
10 up the menu shown in FIG. 14. The user selects "Edit" so as to begin the process of providing constraints to the possible values or expressions the selected variable can assume. However, as can be readily seen from FIG. 14, the system also permits the user to perform other useful functions at this stage.

15 Selecting "Edit" in FIG. 14 brings up the "Create or Change Variable" dialog box of FIG. 15. In accordance with the naming convention, as implemented via the auto-define variabilizing function of the present invention, and as was indicated in the "Variables" window, the variable "SMaleName" in the "Create or
20 Change Variable" dialog box has been classified as a "String" type variable. SMaleName will be a male name selected from a list. The user may at this point, change the variable type, notwithstanding the naming convention, by highlighting and

clicking on any of the other types listed in the "Type" menu of the "Create or Change Variable" dialog box of FIG. 15.

In this preferred embodiment, "Add to checksum" and "Indexed" boxes are selected by default. Selecting the checksum option helps ensure that a value of a variable will be unique; that is, if you want to make sure that all the male names will be different. The "Indexed" option enables the user to assign a particular order to list SmalesName. FIG. 15.

Indexing is particular to Strings. Using indexing, if the user has an item where the stem reads "a lawyer asked his paralegal to call the client", and he/she wanted that to change in some other variant to "a doctor asked his nurse to call a patient". The user would never want to use "lawyer" and "patient" or "nurse" together, or "doctor" and "client" or "paralegal" together. Those three things need to stay together in the items and indexing permits the user to ensure that they do. The user can build sub-strings, so instead of just having String values like John or Mary, the user can have value subsets; for example, where lawyer, paralegal, client always go together and doctor, nurse, patient always go together. As shown in FIG. 16, the user has de-selected "Indexed" and left the remaining options alone.

CREATING AND IMPORTING STRING VALUES

Next the user must provide the available String values and the present invention provides several ways of doing that. One way is simply to click on the "Add" button in Fig. 16. Actually, in this preferred embodiment, everything on the icon bar of the "Create or Change Variable" dialog box of FIG. 15 (and for that matter everything on most of the other icon bars) can also be replicated with a right button click.

Another useful feature of this embodiment is the ability to save the male name String values (or any other list of String values) for subsequent use with different models. The "Exporting Strings" feature is used to save the list and then the "Importing Strings" feature is used to automatically populate the String values of the variable in the new model. Both ways are discussed below.

Using the "Add" Button

Click on the "Add" button in the "Create or Change Variable" dialog box shown in FIG. 16 and the system provides the user with a new dialog box: "Edit string SMaleName". FIG. 17. The user then enters a name, for example John, and then clicks "OK". This procedure is repeated, this time with the String value equal to Tom. FIG. 18. After several more male name String values are inputted the result looks like FIG. 19, where the list of male

names String values all appear, not surprisingly, in the "String values" window. The "Edit" button may be used to edit existing string values.

Using the "Export Strings" and "Import String" Buttons

5 The user can utilize the "Export Strings" function to save this particular list of String values for reuse with another model. The user clicks on the "Export Strings" button shown in FIG. 19 resulting in the "Export string to file" dialog box appearing. The user can then name the file the String values
10 will be saved in (e.g., "male_names") and save the file by clicking on the "Save" button in FIG. 20.

In this preferred embodiment, the file is saved into the directory "TCS/TCA/In. The saved Strings can be shared with other users. If the user needs "male_names" String values, all
15 he/she needs to do is use the "Import Strings" button (e.g., in FIG. 16) and choose the appropriate String file found in the resulting dialog box.

FIGS. 24 through 26 show parts of the above process for providing the String values for the String variables "SItems" and
20 "SFemaleName".

EDITING INTEGER VARIABLES

Select INum1 in the Variables window by making a left mouse button click on INum1 and then make a right mouse button click to open the options menu and "Edit". Once again the "Create or Change Variable" dialog box will appear. FIG. 21. In accordance with the naming convention and the auto-define variables function, "INum1" has been assigned the type "Integer". In the dialog box of FIG. 21 can be found the "Add to checksum" box discussed with respect to String variables and a new box entitled "Independent". FIG. 21. Checking the "Independent" box ensures that the value of the variable will fall into the range of values defined for that variable. If an independent variable (e.g., INum1 in FIG. 22) is not assigned a value in a constraint, a value from the defined range of values (shown in the FROM/TO/BY windows) is chosen at random. If an independent variable (e.g., INum1 in FIG. 22) is assigned a value in a constraint (e.g., "INum1 \neq INum2" (FIG. 49)), the value chosen for the independent variable will still fall within the defined range of values (shown in the FROM/TO/BY windows) chosen at random, but the actual value chosen for the variable will also be required to satisfy the constraint.

When "Independent" is checked a default range of from 1 (its lowest value) to 100 (its largest value) by 1 (or in increments of

1) appears. That is, at this point, INum1 can have the following values: 1,2,3,...,100. FIG. 22. As shown in FIG. 23, the range has been change to from 2 to 26 by 3, and therefore variable INum1 can have the following values: 2,5,8,...,26.

5 In a like manner, the range of values of independent integer "INum2" has been chosen by the user to be 2 to 27 by 5. FIG. 27. Finally, as IKey represents the answer, the user leaves the "Independent" box unchecked as its value will depend upon the values of the variables. FIGS. 28 and 29.

10 SPECIFYING THE CONSTRAINTS

To define relations for determining a value of "IKey" the user can click on "Add" button in the "Variation Constraints" window in FIG. 29. This will bring up the "Create or Change Constraints" dialog box. FIG. 30. This dialog box is divided
15 into three areas. The first entitled "Constraint" is the box wherein variables are constrained. The second comprises three work environments entitled "Operators", "Variables", and "Functions". Clicking on the title/tab activates the chosen
20 environment. Finally, there is a section entitled "Comment" which allows the user to provide comments documenting the particular constraint for use by the current user or another user at some later time.

Operators

The first tab in the box entitled "Operators" appears in bold indicating that the buttons associated with this tab are available to the user. That is, clicking on a button places its operator in the "Constraint" box. The buttons in the "Operators" environment appear in FIG. 30 and comprise mathematical operators: +, -, =, /, %, >, <, >=, <=, if, then, else, elseif, (), etc.

Variables

Clicking on the "Variables" tab, activates the "Variables" environment, and allows the user to enter into the "Constraint" box all currently identified variables. FIG. 31. The user just highlights the variable and clicks on the "Insert" button.

Functions

Clicking on the "Functions" tab, activates the "Functions" environment, and allows the user to enter into the "Constraint" box all TCA library functions. FIG. 32. The user just highlights the variable and clicks on the "Insert" button. Moreover, clicking on a function brings the function to the top box of the "Functions" environment and provides the user with a definition of the function immediately below it. See, for example, FIG. 39.

Constraining "IKey"

The user clicks on the "Variables" tab and selects "Ikey".

FIG. 33. Clicking on the "Insert" button causes the system of the present invention to put "IKey" at the current cursor

location in the "Constraint" box. FIG. 34. Clicking on the

5 "Operators" tab and then clicking on the "=" operator button results in the start of a constraint, namely: "Ikey=". FIG. 35.

Going back and forth from "Variables" to "Operators" and inserting INum1, "+", and INum2 results in FIG. 36. The system allows the direct entry of the constraint in the "Constraint"

10 box, however, providing the ability to pick and choose by clicking facilitates constraint generation, by among other things, reducing typographical errors.

Exporting and Importing Constraints

15 The user can export and import variation constraints in a fashion similar to exporting and importing strings. The "Export Constraints" and "Import Constraints" buttons in the "Model Workshop" are used. FIG. 37. The only difference is that when the user exports or imports constraints the system necessarily exports/imports variables, variable constraints, and associated

20 comments. Clicking on the "Print Constraints" button, FIG. 37, in one embodiment, prints out the constraints.

Constraining the Distractors

Multiple choice tests items are designed to have several responses from which the test taker will choose the correct answer. The correct answer is the key or in this example "IKey". The other responses are wrong answers or distractors and are called "IDistractor_". The user defines as many distractors as the test item calls for, in this example four (4) distractors. To add distractor constraints, the user can click the "Add" in "Distractor Constraints" window, FIG. 38, and the "Create or Change Constraints" dialog box will appear. FIG. 39.

To add an expression for distractor "IDistractor1", the user can either directly type it in the "Constraint" window/box or insert it by going to the "Functions" tab, selecting a function from the list, and inserting it by clicking on the "Insert" button. When a function is selected, a useful description of the function is displayed to the user. FIG. 39. Variables can be inserted into functions, for example, "INum1" and "INum2" into "min()". See FIGS. 39-41. Clicking on the "OK" button in the "Create or Change Constraints" dialog box finishes defining the constraint for the time being and all the constrained distractors appear in the "Distractor Constraints" window of the Model Workshop. See, e.g., FIG. 42.

Testing the Constraints

The systems permits the user to test the constraints by testing selected or all variables, variation (variable) constraints, and distractor constraints. The user checks off all the items to be tested and depending on the circumstances clicks on the "Test" buttons on the icon bar at the bottom of the appropriate Workshop window or the "Test All" button to the right of those windows. The ability to chose particular items to be tested is very helpful in locating the source of any problem.

FIG. 42. After TCA finishes testing all checked variables and

constraints in FIG. 42, a "Test Result" window appears. FIG. 43.

The "Test Result" for FIG. 42 was "Variable IDistractor4 is underconstrained!" In fact, it had not been constrained. After constraining IDistractor4 and clicking on the "Test All" button

appears the next "Test Result". FIG. 44. This time TCA tells

the user that the constraints "Looks Good!". If the constraints "Looks Good!" the next step is to click on Generate Variants" tab so as to be able to use TCA to automatically generate test item variants based on the model developed in the Model Workshop.

FIG. 45.

GENERATING TEST ITEM VARIANTS

To generate variants all the user needs to do is enter the number of variants to be generated in the "Number" box and click

on the "Generate" button. FIG. 45. The user can also adjust the "Prolog randomization". The generated variants will appear in the "Variants" window. In this case the system was requested to generate two (2) variants from family model "NEWMC\$R.DOC". The variants generated from this model have names NEWMC\$R1.doc and NEWMC\$R2.doc. That is, family model name variant number 1 and number 2. FIG. 46. Selecting a variant in the "Variants" window causes the variant to be displayed in the Microsoft® WORD window. Note that at least three of the distractors for test item

NEWMC\$R1.doc equal the same value, namely, 6. Therefore, as initially constrained the distractors in this model can simultaneously have the same value, which is wrong. Therefore, the user will need to change the constraints to eliminate this possibility.

If based upon a review of the generated variants the user wishes to modify the constraints, he/she need only click on the "Model Workshop" tab. If the user does so, a warning appears to the effect that variants on tab 3 (the "Generate Variants" tab) will be deleted if not saved before changing the model. FIG. 47.

FIG. 48 shows part of the process of adding a new constraint in an attempt to resolve the distractor problem. The new constraint is that INum1 cannot equal INum2. Adding this constraint and then testing results in a "Looks Good". FIG. 49.

FIGS. 50 - 51 show the result of generating 2 variants from the new model. It appears that the distractor problem has been fixed.

WORKING WITH GENERATED VARIANTS AND GENERATING NEW MODELS

5 ACCEPTING VARIANTS

10 If the user is satisfied with one or more generated test item variants, the variants may be accepted. Selecting the variant "NEWMC\$R3.doc" and clicking on the "Accept" button in FIG. 52 leads to FIG. 53 where a dialog box entitled "Confirm" appears and the user is given one more chance to accept the variant or not. Since the user chose to accept the variant, it no longer appears in the "Variants" window of the "Generate Variants" tab. See FIG. 54.

DEFERRING AND DISCARDING VARIANTS

15 If the user does not "like" a variant, the variant can either be deferred by selecting and clicking on the "Defer" button, or discarded by selecting and clicking on the "Discard" button. FIG. 54. In deferring a variant, this preferred embodiment of TCA does not store the variant's check sum value, 20 therefore, deferred variants could be generated again. On the other hand, discarded variant check sums are stored to ensure that they will not be regenerated in the future.

CREATING NEW VARIANT MODELS FROM A GENERATED VARIANT

To create a new variant model (new children of the active model) from a particular variant, select the variant in the "Variants" window and click on the "Create Mdl." (Create Model) button on the icon bar located at the bottom of this window.

FIG. 54. A dialog box entitled "Confirm" will appear, the user clicks on the "Yes" button, FIG. 54, to create a new model. The new model creation is confirmed by a dialog box entitled "Model Created". FIG. 56. Thus confirming that the variant has been copied with a new name. The name of the new model appears in the "Model Created" dialog box. In this case, the new model is named "NEWMC\$RA.doc". The "R" means that the model is a root model, the "A" at the end of the name implies that it is a child of the model "NEWMC\$R.doc". FIG. 56. In this way, the variables and the constraints of the previous model are preserved, so the user does not have to go in and start variabilizing from the beginning.

ACCEPTED VARIANTS AND NEW FAMILY MODELS

If the user clicks on the "Family Overview" tab, FIG. 57, "NEWMC\$RA.doc" appears in the "Family members" window. A sun icon next to this name indicates that the model is active. The "snowflake" icon to "NEWMC\$R.doc" indicates that this model is "frozen". As soon as at least one item variant generated from an

item model is accepted, the item model is frozen. A frozen item model can be viewed and used to generate more item variables and unfrozen child models, but the model is blocked to future changes. Finally, the accepted variant "NEWMC\$R3.doc" appears in the "Accepted variants" window. FIG. 57.

WORKING WITH MODELS AND ACCEPTED VARIANTS

ISS #67 To begin working with the new model "NEWMC\$RA.doc" click on the name and the model will appear in Word® window. FIG. 58.

Click on "Set Attributes" button in FIG. 58 brings up the "Family Attributes" dialog box. FIG. 59. The user has the option of choosing either "Generic" or "Non-generic". Variants are considered "generic variants" if they are very familiar in terms of structure and content, otherwise variants are called "non-generic variants". The user also has the option of choosing the "Variant proximity". As can be seen in FIG. 60 the proximity can be "Near", "Medium" or "Far". Clicking "OK" after making the appropriate selections in the "Family Attributes" box associates the selections with the model.

To "extend" (make a copy) or remove a "frozen" model or "unfrozen" model, the user selects the item, right mouse-button clicks, and selects "Extend" or "Remove". FIG. 61. The same could be done by using buttons "Extend" and "Remove" that are

located on the bar at the bottom of the "Family members" window.

FIGS. 61 - 62.

EDITING THE PROFILE OF A VARIANT

5 To edit or copy the profile of an accepted variant, select the variant and click on the "Edit Profile" or "Copy Profile" button as appropriate. They are located on the bar at the bottom of "Accepted variants" window. FIG. 63. Clicking on "Edit Profile" brings up the "Profile of variant [name of variant]"

10 dialog box. FIG. 64. Clicking on the arrow next to the "Domain:" window in FIG. 64 brings down the selection of domains: Arithmetic, Algebra, Data Analysis, or Geometry. FIG. 65. Clicking on the arrow next to the "Target template:" window in FIG. 64 brings down the selection of targets: "CBT" for computer

15 based testing or "PPT" for paper and pencil testing. FIG. 66.

 The user can also select either "Pure" or "Real" shown for example in FIG. 66. A Pure test item is one in a mathematical setting. A Real test item is one that is based on a real-life situation. The user can also select Route to TCS (ETS' Test

20 Creation System) shown for example in FIG. 66. ETS' Test Creation System is disclosed in U.S. Patent No. 6,000,945, which is hereby fully incorporated by reference herein.

The GRE Difficulty Portion of the Profile of a Variant Window

The "GRE Difficulty" portion of the Profile of variant window shown in FIG. 67, for example, has several components.

Clicking on the arrow next to the "Computation:" window, brings

5 down the following selection which denotes the type of numbers

used in the test item: Integers, Decimal/fractions, Radicals, or

Not applicable. FIG. 68. In the same fashion, the "Cognition:"

window provides selections for denoting the sort of process the

test item requires the test taker to go through to arrive at the

10 answer, namely: Procedural, Conceptual, or Higher order

thinking. FIG. 69. The "Concept" window provides selections for

denoting the basic concepts tested by the item, namely:

Probability, Percent of a percent, Percent change, Linear

inequality, or Not applicable. FIG. 70. "Adjust the slide to

15 estimated difficulty:" allows the user to denote his or her

opinion of the difficulty of the variant. See, for example, FIG.

70. The "Key:" window allows the user to denote the correct

answer. Finally, the "Predicted Difficulty" or IRT b measure is

calculated from other entries in the window (e.g., whether the

20 item is arithmetic or algebra).

WORKING WITH FAMILY MEMBERS

Back at the "Family Overview" window, FIG. 71, by selecting the "frozen model" "NEWMC\$R.doc", right mouse-button clicking, and selecting "Extend", the user can extend the "NEWMC\$R.doc".

5 In response to selecting "Extend", the "Confirm" window pops up, FIG. 72 and clicking on "Yes" extends the model. New active model "NEWC\$RB.doc" then appears in the "Family members" window. FIG. 73.

Using a New Active Model to Generate Far Variants

10 The new model is immediately available for the user. Clicking on the Model Workshop tab for "NEWC\$RB.doc" brings the user to a place where he or she can modify the model. For example, the user could replace the stem:

15 "If SMaleName had INum1 SItems and SFemaleName had INum2 SItems, how many SItems would they have together?";

with "SStem"; add "SStem" as a new variable; and add

20 "If SMaleName had INum1 SItems and SFemaleName had INum2 SItems, how many SItems would they have together?";

as a String value for "SStem". See FIG. 73A. The user could also add other values for "SStem", for example,

"INum1 + INum2 = ?".

FIG. 73B. Thus, this preferred embodiment of the present invention allows the user to easily generate far variants (variants that are very different from one another) from this new stem by going to "Generate Variants", requesting 2 variants, FIG. 5 73D, and clicking on the "Generate" button. Thereby generating new variants "NEWMC\$RB3.doc", FIG. 73D and "NEWMC\$RB4.doc", FIG. 73E.

Creating Still More Models

10 Preferred embodiments of the present invention permit the user to make a child model from the "NEWC\$RB.doc" model of FIG. 73, that is, to extend it. The user selects "NEWC\$RB.doc", clicks on the "Extend" button, and then enters "Yes" in the "Confirm" window, FIG. 74. New active model "NEWC\$RBA.doc" 15 appears. FIG. 75. Left button click to select this model, then right mouse button click to extend it or remove it. FIG. 75. To make a child model from new model "NEWC\$RA.doc", repeat the above procedure, New active model "NEWC\$RAA.doc" appears. The "AA" stands for a child of a child of the root model. See, FIGS. 76 - 20 77.

The constraints for any of the active models that are displayed in the "Family members" window can be changed. To change the constraints, select an active model in the "Family

members" window, click on tab Model Workshop, left button click to select a constraint, and then right button click to get the constraint option. FIG. 78.

5

PRINT OPTIONS

To print accepted variants click on tab "Family Overview" and then click on button "Print All" in FIG. 79. FIGS. 80A, 80B and 80C is the result. It is a print out of the variables and constraints for model "NEWMC\$R". Selecting the model "NEWMC\$RA" as the active model and in the Model Workshop clicking on the "Print Constraints" button in FIG. 81, results in a print out of the variables and constraints for model "NEWMC\$RA". See, FIGS. 82A, 82B, and 82C.

15 *DESA 7* To print a model without constraints click on the "Family Overview" tab and select a model, for example NEWMC\$R.doc. In the Microsoft® WORD window entitled "NEWMC\$R.doc", select File and Print or just click on print button. The result is a print out of model "NEWMC\$R.doc" without constraints. See FIG. 83.

20 To print one of the accepted variants from a particular model, click on "Family Overview" tab, select a model, for example "NEWMC\$R.doc". In "Accepted variants" window, select one or more variants, for example "NEWMC\$R3.doc", "NEWMC\$R4.doc",

etc.. In the Microsoft® WORD portion for each variant print out the document. The test item variants appear in FIGS. 84 - 88.

GRE QUANTITATIVE COMPARISON ITEMS

5 To create a model for GRE Quantitative comparison items, the user starts as shown in FIGS. 1-3. However, instead of keeping Multiple choice as an item choice, "Quantitative comparision" is selected. FIG. 89. "Non-generic" and "Near" are also chosen is the example to be discussed. After saving this new family as
10 "NEWQC" the result is FIG. 90.

105 AB In the Microsoft® WORD document appears the title "TCA Quantitave Comparison Model"; there are also sections entitled "reserved for variants", "stem", "column A", and "column B". In the right part of the window you will see "Family Overview" tab
15 highlighted. In "Family members" you will see an icon with a sun and the name of the chosen variant, "NEWQC", next to it. The variant family name will have an extension "\$R.doc". The "sun" icon again indicates that the model is active. In the "Family members" window appear two highlighted buttons: "Extend" and
20 "Remove". These buttons enable the user to extend or remove the variant family, respectively. At the bottom of the "ETS Test Creation Assistant" window, you will see a toolbar with following titles: "Program -GRE", "Family -NEWQC\$R.doc", "Attributes - QC",

"Non generic", "Near", / "Active Model . . . "NEWQC\$R.doc". FIG.
90.

FIG. 91 is a print out of "NEWQC\$R.doc". The idea of a QC
item is to compare values in columns A and B. FIG.91.

5

GMAT DATA SUFFICIENCY ITEMS

To create a model for GMAT Data Sufficiency items the
approach is generally the same as with the other item types
taking into account the concept behind the item type. See FIGS.

10 92 - 93.

FURTHER EXAMPLES OF ITEM MODELS

See FIGS. 94 - 106B for further examples of item models.

15

PROLOG SIMULTANEOUS CONSTRAINT SOLVER

Preferred embodiments of the present invention use PROLOG as its simultaneous constraint solver. Details of one preferred embodiment appear in the PROLOG SOURCE CODE APPENDIX. Brief descriptions of the TCA Prolog (and Prolog-related) files are provided below.

HLP4lib.p4

This file provides a library of Prolog-predicates for use in solving mathematical constraints. For example, it provides a Prolog predicate gcd(GCD, A, B) returns the GCD of two integers A and B. This file provides a library of Prolog IV accessory relations useful in high-level API.

PrlgExpr.l

This file provides the lexical specification for the Prolog-expression scanner. Using this file, an appropriate scanner is generated. The scanner breaks the mathematical constraints into individual words and operators (called tokens) which are further used by the Prolog-expression parser.

PrlgExpr.y

This file provides the syntactic specification for the Prolog-expression parser. The file PrlgExpr.y provides the BNF-specification from which the parser-code is generated. While PrlgExpr.y is "almost" a parser, it contains, strictly speaking,

a specification to generate a parser. Therefore, using this file, an appropriate parser is generated. The parser accepts the tokens from the scanner, and recognizes the syntactic patterns of mathematical constraints (or parses mathematical constraints or computes a parse-structure for mathematical constraints). Having recognized the syntactic patterns, it transforms the mathematical constraints into appropriate Prolog clauses, and calls Prolog IV to solve those clauses.

hlp4API.h

This file provides a specification for API access to the mathematical constraints-solver, Prolog IV. Using this specification, other programs can access the constraints-solver to solve mathematical constraints.

TCA CONSTRAINT LANGUAGE

TCA uses a high-level language derived from Prolog and Algebra to write mathematical constraints. This section describes the language and provides some example mathematical constraints.

The TCA constraint language is intended to help the test developers in writing models for math items to be cloned. As such, it is a language very similar to the test developers' language of choice: the mathematical notation to write algebraic equations. It provides a suite of predefined high-level functions to choose from, high-level set operators (e.g. membership/iteration over a continuous range or a discrete set), and additional operators (e.g. and, or) to combine the constraints in the desired fashion.

The TCA constraint language differs from procedural languages (e.g. C, Fortran) principally in that it is a goal-oriented language, that is users need specify only the constraints to be solved, and not how to solve them. In addition, the TCA constraint language has (almost) no program-flow control mechanisms (e.g., no goto's, no while loop). Program-flow is controlled by the constraint-solver. Further, as expected from a mathematical constraint-solver, it is

constraint-order independent (e.g. $X = 2$, $Y = X + 2$. can equally well be written as: $Y = X + 2$, $X = 2$.).

NOTATIONAL CONVENTION

Solutions follow the arrow (\Rightarrow) after the constraint.

5 Item^* represents 0 or more instances of Item.

Item^+ represents 1 or more instances of Item.

$\text{Item}?$ represents 0 or 1 instance of Item.

func/n represents a function with n arguments, for example, $\text{max}/2$ represents the function max with two arguments (e.g., $\text{max}(4, 7)$), while $\text{max}/1$ represents the function max with 1 argument (e.g. $\text{max}([4, 7])$).

In describing the arguments to a function, the notation $+\text{Arg}$ is used to indicate that the value of the Arg must be given (i.e., Arg is an input argument), and

15 $-\text{Arg}$ to indicate that the value of the given Arg is set by the function (i.e., Arg is an output argument). A simple

Arg (without $+$ or $-$) indicates that one can use the argument with input or output parameter.

TCA CONSTRAINT LANGUAGE IN DETAIL

20 The TCA constraint language (often referred to herein as the language) is syntactically based on conventional mathematical notation system, with some additional syntactic constructs to combine multiple constraints in various ways (e.g., conjunction,

disjunction, if-then-else) and to supply some low-level details often hidden in mathematical notations (e.g., type, precision, stepsize for iteration). Note that the TCA constraint language is case-sensitive; e.g., Xvar is different from xvar.

5 The TCA constraint solver can solve linear constraints and a large class of nonlinear constraints. The user need specify only the constraints to be solved, and not how to solve them. The TCA returns all the solutions to the specified constraints. Further, all the constraints and functions are relations which have

10 minimal input/output directional restrictions; i.e., one can use the same argument in a function to provide a known parameter and to compute an unknown value. For example, one can use the same constraint $Z*Z = X*X + Y*Y$ in multiple ways:

 Given $X (:3)$ and $Y (:4)$, to compute the value of Z ; i.e.:

15 $X = 3, Y = 4, Z*Z = X*X + Y*Y. \Rightarrow \{Z: 5; Z: -5\}.$

 Given $Z (:5)$, to compute the possible values for X and Y ;

 i.e.: $5*5 = X*X + Y*Y, \text{int}(X, Y). \Rightarrow \{X: 3, Y: 4; X: 4, Y: 3\}.$

 Given $Z (:5)$ and $X (:3)$, compute the value of Y ; i.e.: $5*5 = 3*3 + Y*Y. \Rightarrow \{Y: 4\}.$

20

The constraints in the language are specified using a combination of the representational devices offered by the language: basic

elements, type specifications, set specification, algebraic constraints, logical combinations.

BASIC ELEMENTS

Basic elements are the basic objects of the language. These
5 elements are later referred, in general, as the terms.

1. Constants.

a) Numbers: 4, 10, -4, 5.6, -6.7.

b) Symbolic number: pi.

c) Symbolic constants (atom): Symbolic constant-names must start
10 with a lowercase letter. For example, countVar, accountant. Any
alphanumeric symbol that starts with a lowercase letter is
considered a constant. Symbolic constants may not occur in an
algebraic constraints: "X = 5 + accountant" is invalid.

2. Variables.

15 Variable-names must start with an uppercase letter: X, Xin,
Yout. Note that case (uppercase, lowercase) is important. For
example, X is a variable whereas x is a constant.

A special variable, called anonymous variable, may also be
used. An anonymous variable is written as: "_ ". An anonymous
20 variable acts like a placeholder, as a don't-care variable. Each
anonymous variable, even when used multiple times within the same
constraint, is distinct and one may not refer to it. For
example, function divmod(N, D) returns a list: [N div D, N mod

D]. However, in case one is not interested in, say, the mod-result (i.e. the second member of the list), one could write:

```
[Div, _ ]= divmod(N, D) .
```

3. Lists.

5 A list of variables, constants, other lists using the
format: [elements*], e.g.: [], [a, b, c], [1, 2, 4, 7], [1,
[2, 3, 4], C, 7]. One can access the elements of the list using
the notation: ListName [Index1 [, Index2 [, Index3 ...]]].
Note that the first element of the list is indexed 1, second
10 element is indexed 2, and so on. Multiple indices are used for
multilayered lists; lists containing lists as elements: [[a, b],
[c, d]]. Multilayered lists can be used to represent tables.
Some constraints involving lists and list-elements and their
solutions are shown below:

```
15 L= [1, 3, 5, 7], X= L[2].                    =>    X: 3.  
L= [[1, 3], [5, 7], [9, 11]], X= L[2].        =>    X: [5, 7].  
L= [[1, 3], [5, 7], [9, 11]], X= L[2, 1].    =>    X: 5.  
L= [[1, 3], [5, 7], [9, 11]], X= L[2, 2].    =>    X: 7.  
L= [[a, [b, c]], [d, [e, f]]], X= L[2, 2].   =>    X: [e, f].  
20 L= [[a, [b, c]], [d, [e, f]]], X= L[2, 2, 1]. =>    X: e.
```

4. Functions.

In accordance with the present invention, functions predefined in the constraint language can be used. General format

for a function-call is: function-name(args*). For example,
abs(X) or mean(A, B) or median([1,4,3,7, 9]).

Note that the functions return values of the types indicated
below. The functions are valid only when their return-values are
in the appropriate context. That is, functions returning numbers
must be in the context of the algebraic expressions (e.g.

(assuming X is a variable of type number): X= sqrt(25));

functions returning lists must be in the context of the list
expressions (e.g. (assuming L is a variable of type list) : L=

sort([1,7,5,3,2])); functions returning symbols must be in the
context of the symbol expressions (e.g. even(4)= true.).

The predefined functions for one preferred embodiment are listed
below with the following notational convention:

The return-type of a function is indicated as: =>

Return-Type.

Names of the function-arguments of type integer start
with I;

Names of the function-arguments of type real start with
R;

Names of the function-arguments of type number start
with N;

Names of the function-arguments of type
lists-containing-numbers start with NL;

Names of the function-arguments of type list
(containing any kind of elements) start with L).

The predefined functions include:

max(+N1, +N2) (\Rightarrow Number) Returns the maximum of
5 numbers N1 and N2 e.g. $X = \max(4, -5)$.

max(+NList) (\Rightarrow Number) Returns the maximum of
a list of numbers e.g. $X = \max([2, \sqrt{9}])$.

min(+N1, +N2) (\Rightarrow Number) Returns the minimum of
numbers N1 and N2 e.g. $X = \min(4, -5)$.

10 min(+NList) (\Rightarrow Number) Returns the minimum of a
list of numbers e.g. $X = \min([2, \sqrt{9}, 2^2])$.

mean(+N1, +N2) (\Rightarrow Number) Returns the mean of numbers
N1 and N2 e.g. $X = \text{mean}(4, \sqrt{9})$.

15 Mean(+NList) (\Rightarrow Number) Returns the mean of a list
of numbers e.g. $X = \text{mean}([2, \sqrt{9}, 2^2])$.

median(+NList) (\Rightarrow Number) Returns the median of a list
of numbers e.g. $X = \text{median}([2, \sqrt{9}, -4, 7])$.

gcd(+IN1, +IN2) (\Rightarrow Integer) Returns the gcd of integers
IN1 and IN2 e.g. $X = \text{gcd}(4, 6)$.

20 lcm(+IN1, +IN2) (\Rightarrow Integer) Returns the lcm of integers
IN1 and IN2 e.g. $X = \text{lcm}(4, 6)$.

sqrt(N) (\Rightarrow Number) Returns the positive
square-root of (positive number) N e.g. $X = \sqrt{20}$.

cubert(N) (= > Number) Returns the cube-root of
(positive number) N e.g. X= cubert(20).

reverse(+List) (= > List) Returns the reversed List e.g.
X= reverse([1,2,3,7,5]).

5 sort(+NList) (= > List) Returns the list of numbers
sorted in numerically ascending order e.g. X=
sort([1,2,5,3]).

permute(+List) (= > List) Returns the various
permutations of the given List e.g. X= permute([1,2,3]).

10 select_r_of_n_ordered(IN, IR) (= > Integer) Returns no.
of ordered subsets of size IR from the set of size IN.

select_r_of_n (IN, IR) (= > Integer) Returns no. of
unordered subsets of size IR from the set of size IN.

15 random() (= > Integer) Returns a randomly
generated integer e.g. X= random().

random(+List) (= > Same-as-the-Given-List-Element)
Returns a random element from the given list e.g. X=
random([a,2.5,6,c]).

20 random(+IMax) (= > Integer) Returns a random integer
between 1 through (positive integer) IMax e.g. X= random(7).

even(+IN) (= > true) Returns literal constant true
if IN is an even integer e.g. even(10)= true.

odd(+IN) (=> true) Returns literal constant true
if IN is an odd integer e.g. odd(11)= true.

is_perfect_square(+IN) (=> true) Returns literal
constant true if IN is a perfect square e.g.

5 perfect_square(16)= true.

isnot_perfect_square(+IN) (=> true) Returns literal
constant true if IN is not a perfect square e.g.
isnot_perfect_square(17)= true.

10 is_perfect_cube(+IN) (=> true) Returns literal
constant true if IN is a perfect cube e.g.
perfect_square(64)= true.

isnot_perfect_cube(+IN) (=> true) Returns literal
constant true if IN is not a perfect cube e.g.
isnot_perfect_square(25)= true.

15 is_prime(+IN) (=> true) Returns literal constant true
if IN is a prime integer e.g. is_prime(11)= true.

isnot_prime(+IN) (=> true) Returns literal constant
true if IN is not a prime integer e.g. isnot_prime(10)=
true.

20 5. Algebraic Expressions (referred to as: AlgExpr).

Expressions can be built by combining other algebraic
expressions (e.g. numbers, variables, functions) using the
arithmetic operators. Valid operations include:

"+" (addition): AlgExpr + AlgExpr, e.g. A + B, or 4 + C, or sqrt(16)+7.

"-" (subtraction): AlgExpr - AlgExpr, e.g. A - B, or 4 - C, or sqrt(16)-7.

5 "Unary -" (unary negation): - AlgExpr, e.g. -B, or -7.

"*" (multiplication): AlgExpr * AlgExpr, e.g. A * B, or 4 * C, or sqrt(16) *7.

10 "/" (division): AlgExpr / AlgExpr, e.g. A / B, or 4 / C, or sqrt(16) /7.

"%" (modulo): AlgExpr % AlgExpr, e.g. A % B, or 4 % C, or sqrt(16) %7.

"\" (quotient): AlgExpr \ AlgExpr, e.g. A \ B, or 4 \ C, or sqrt(16) \7.

15 "^" (exponentiation): AlgExpr ^ AlgExpr, e.g. A ^ B, or 4 ^ C, or sqrt(16) ^7.

"!" (factorial): AlgExpr!, e.g. A!, or 4!.

"|" (abs): | AlgExpr |, e.g. |A - 10|, or | sqrt(16) -7|.

20 The precedencies of the arithmetic operators are as follows (higher precedence operators are specified before the lower precedence once): !; ^; - (unary negation); % & \; /; *; + & - (subtraction); | ... |.

CONSTRAINT SPECIFICATION

1. Type Constraint Specification.

These constraints specify the type of the variables in the constraint. The default variable type is "real".

5	"int(VarLst)"	e.g.: int(X), int(X, Y).
	"real(VarLst)"	e.g.: real(Y), real(X, Y).
	"fraction(VarLst)"	e.g.: fraction(X), fraction(Y, Z).
	"symbol(VarLst)"	e.g.: symbol(X), symbol(Y, Z).
	"list(VarLst)"	e.g.: list(X), list(X, Y).
10	"ongrid(Var)"	Specifies that the value of the given variable must be an integral multiple of its precision. [This is the default behavior of the variables.] e.g.: ongrid(X).
15	"offgrid(Var)"	Specifies that the value of the given variable need not be an integral multiple of its precision. e.g.: offgrid(X).

2. Optimizable-Relation Specification.

20 A user may help the constraint-solving process by
identifying the optimizable relations. Such relations must be
valid for the entire constraint (i.e., they may not be a part of
a disjunctive clause), and they may be moved around by the

constraint-solver without any logical incorrectness, usually to the start of the clause.

The devices to identify such relations include:

"eq_vars(Vars)"	Variables in the given comma-separated- list must be equal to each other. e.g.: eq_vars(X, Y, Z).
"neq_vars(Vars)"	Variables in the given comma-separated- list may not be equal to each other. e.g.: neq_vars(X, Y, Z).
"neq_varvals(Var, Vals)"	The given variable may not be equal to any of the values specified in the comma-separated-list. e.g.: neq_varvals(X, 2, 5, 7).
"optimizable_rel(Relation)"	The specified Relation is optimizable. This is a generalization of the special optimizations presented above. e.g.: optimizable_rel(X/=5).

Note that neq_vars(X,Y) (and, similarly, eq_vars(X,Y)), while semantically equivalent to $X \neq Y$, is operationally different from

$X \neq Y$ in that the constraint-solver optimizes such declarations (which it cannot do in case of declarations such as: $X \neq Y$ or $X=Y$).

3. Precision Specification.

5 Constraints are solved with certain precision. The default precision is: 0.01 for reals, 1 for integers. Nonlinear constraints are solved by enumerating through the potential solution-interval. A variable may assume a value which must be an integer multiple of its precision.

10 Precision for a variable can be changed individually by using the following construct for the variable in the type-specification: {Var, Precision}. For example, `real({X, 0.02})` specifies a precision of 0.02.

4. Relational Constraints (RelExpr).

15 Valid relational constraints (and the associated relational operators) include:

"=" (equality): AlgExpr = AlgExpr, e.g. $A = B$,
 $A + 5 * Z = \text{sqrt}(16) + C$.

"!=" (inequality): AlgExpr != AlgExpr, e.g. $4 * X +$
20 $5 * Y \neq 2 * A + 3 * B$.

"<" (less than): AlgExpr < AlgExpr, e.g. $A < B$, $A +$
 $4 * Z < 4 + C$.

">" (greater than): AlgExpr > AlgExpr, e.g. $A > B$, $A + 4 * Z > 4 + C$.

"<=" (less than or equal to): AlgExpr <= AlgExpr e.g. $A <= B$, $A + 4 * Z <= 4 + C$.

5 ">=" (greater than or equal to): AlgExpr >= AlgExpr, e.g. $A >= B$, $A + 4 * Z >= 4 + C$.

"NOT": NOT RelExpr, e.g. NOT(is_prime(X) = true).

5. Ranges.

10 "Continuous interval": To specify a variable Var within a continuous range: [LowerExpr RL Var RL UpperExpr] where RL is one of the relational operators: { <, <=, >, >= }, e.g. to specify the constraint that X may range from 0 through 10: $[0 \leq X \leq 10]$.

15 "Continuous exterval": To specify a variable Var outside a continuous range: [! LowerExpr RL Var RL UpperExpr] where (RL is one of the relational operators: { <, <=, >, >= }.) For example, to specify the constraint that X must be outside the range from 0 through 10: $[! 0 \leq X \leq 10]$.

20 "Discrete inclusive range": To specify a variable Var within an enumerated range: Var in [Expr1, Expr1, ...]. For example, $X \text{ in } [1, 5, 4+3, a, Y^2, 15]$, or, $X \text{ in } [1, 2*Y + Z, 7, Z]$. The Var assumes each value from the given set of values.

"Discrete exclusive range": To specify a variable Var outside an enumerated range: Var notin [Expr1, Expr2, ...]. For example, X notin [1, 5, 4+3, a, Y^ 2, 15], or, X notin [1, 2*Y+Z, 7, Z].

5 6. Enumerated Ranges.

To specify an enumerated range, we use: [LowerExpr RL Var RL UpperExpr step Expr] where (RL is one of the relational operators: { <, <=, >, >= }). Thus, for example, to specify that (a real variable) X enumerates through the range from 7
10 though 10 by a step of 0.5: [7<= X<= 10 step 0.5]. The example constraint is equivalent to: (X= 7; X= 7.5; X= 8; X= 8.5; X= 9; X= 9.5; X= 10).

To specify a discrete enumerated range, we use: Var from List. Thus, for example, to specify that (a variable) X can take
15 one of the values from the set [a, b, c, d], we use: X from [a, b, c, d]. Similarly, to specify that another variable Y can take a value from the set of primes between 2 and 10, we can use: Y from [2, 3, 5, 7] .

If a continuous enumeration range is not closed on lower
20 [upper] side (e.g., left relational operator is <), the lower [upper] expression is incremented [decremented] by the variable-precision for expanding the enumeration range. Thus, for example, for a real variable X with precision of 0.1, [7< X<

10 step 0.5] . => (X= 7.1; X= 7.6; X= 8.1; X= 8.6; X= 9.1; X= 9.6).

Note that an enumerated range is different from a regular (i.e. non-enumerated) range. The difference is especially visible for open (or, partially closed) ranges. For example, for a real variable X with precision of 0.1, the constraint: [7< X< 10 step 0.5], X= 7.4. is not successful, but the constraint: [7< X< 10], X= 7.4. succeeds.

Further, the main-variable in an enumerated range is considered independent, whereas the main-variable in a non-enumerated range is not independent. This difference becomes important when one is trying to generate different solutions for a constraint from the solver. While solving for different solutions, the constraint-solver tries to find different values for the independent variables in different solutions. It makes no such effort for non-independent variables.

Note that a user may not use variables in specifying the boundary(s) of an enumerated range when solving the constraints in the unique-order. As such, when solving the constraints in unique order, an enumeration range such as: [C+1 <=X <= C+3 step 1] is not acceptable because it uses variables in specifying the boundaries of the enumerated range.

7. if-then-else Constraint.

if (Condition) then (Then-Constraint) else
 (Else-Constraint). For example, if (is_prime(X)= true) then (Y=
 found_an_x_as_prime) else (Y= no_x_is_prime). (if-then alone
 also be used e.g. if (X== 5) then (Y= 7).)

5 Note that the semantics of the if-then-else constraint is:
 if Condition is ever true, then only the Then-Constraint is
 tested (i.e. executed). Only when the Condition is never true,
 the Else-Condition is tested (i.e. executed). Thus, for example,
 the following if-then-else constraint produces the results shown

10 below:

```
int(X), [1<=X<=4 step 1], if (even(X)= true)
then Y= x_is_even else Y= x_is_odd.    =>
X: 2, Y: x_is_even;
X: 4, Y: x_is_even.
```

15 Refer to the if-then-elseif constraint for a slightly different
 kind of constraint.

8. if-then-elseif Constraint.

20 if (Then-Condition) then (Then-Constraint) elseif
 (Else-Condition) then (Else-Constraint). e.g. the following
 constraint produces the absolute-values of X:

```
if (X>= 0) then (Y= X) elseif (X< 0) then (Y= -X).
```

Note that the semantics of the if-then-elseif constraint is:
 if Then-Condition is true, then the Then-Constraint is tested

(i.e. executed); or if Else-Condition is true, then the Else-Constraint is tested (i.e. executed). Thus, for example, the following if-then-elseif constraint produces the results shown:

```
5      int(X), [1<=X<=5 step 1], if (even(X)= true)
      then Y= x_is_even elseif (odd(X)= true) then
      Y= x_is_odd.    =>
```

```
      X: 1, Y: x_is_odd;
```

```
      X: 2, Y: x_is_even;
```

```
10     X: 3, Y: x_is_odd;
```

```
      X: 4, Y: x_is_even.
```

Refer to the if-then-else constraint for a slightly different kind of constraint.

9. Freeze Constraint.

```
15      Usually, one is interested in exploring the entire
      solution-space. However, there are times when one is satisfied
      with the solution (set) received so far, and wishes to freeze the
      solution (set) discovered so far. The freeze constraint is
      represented by the keyword: freeze.
```

20 10. Primitive succeed and fail constraints.

One can force a constraint to fail by conjuncting fail with it. Thus, for example, `X= 4, fail. => false.` Similarly,

succeed succeeds vacuously e.g. if $(X > 4)$ then succeed else fail.

11. Period (.) at the end of constraints.

12. Combining Constraints.

5 Grouping constraints together: "(Constraint)".

For example, $(X = 4 + X, Y = 2)$.

Conjunction (and): "Constraint1 , Constraint2".

For example, $X * X = 25, Y = 5, X = Y. \Rightarrow \{X: 5, Y: 5\}$.

Disjunction (or): "Constraint1 ; Constraint2".

10 For example, $X * X = 25; Y = 5, X = Y. \Rightarrow \{X: 5; X: -5; X: 5, Y: 5\}$.

Negation: "NOT Constraint".

For example, $\text{NOT}(X = 5)$.

Note that $\text{NOT}(X = 5)$ (i.e., it is never the case that X is 5) is not equivalent to $X \neq 5$ (i.e. the case when X is not 5). Thus:

15 X in $[1, 2], X \neq 1$. produces only one answer: $X: 2$ (because $X \neq 1$ succeeds when $X: 2$), whereas: X in $[1, 2], \text{NOT}(X = 1)$. fails (because $X = 1$ succeeds when $X: 1$).

WRITING CONSTRAINTS IN TCA CONSTRAINT LANGUAGE

20 The TCA constraint language combines the algebraic language with the syntax and semantics of logic programming language (for example, Prolog). It differs considerably from the procedural programming languages (for example, C, Fortran) which rely on

program-flow control to specify a procedure to solve the problem at hand. Major differences between procedural languages and the TCA constraint language of the present invention include:

TCA constraint language is declarative: In the TCA
5 constraint language, one specifies only the constraints to be solved, not how to solve them.

Constraints are order-independent: In the TCA constraint language, the constraints are order-independent e.g. $X = 2$, $Y = X + 2$. is the same as: $Y = X + 2$, $X = 2$. In procedural languages,

10 statements are order-dependent, e.g. in C, $X = 2$; $Y = X + 2$; is different from: $Y = X + 2$; $X = 2$. An exception to the order-independence of rules is the case where we use the continuous-range constraint (e.g., $[2 \leq X \leq 5]$) for integer variables and invoke functions with the variable from the
15 continuous range (e.g., $Z = \text{gcd}(X, Y)$). In such situations, the solver's behavior depends on the relative position of the variable-type-declaration (e.g., $\text{int}(X)$) vs. the continuous range declaration (e.g., $[2 \leq X \leq 5]$). In general, the user of the present invention should put the variable-type-declaration as
20 soon as he/she knows it. For example, $\text{int}(X)$, $Y = 5$, $[2 \leq X \leq 10]$, $Z = \text{gcd}(X, Y)$.

Constraints are solved all at once as a whole.

TCA constraint language provides its own program-flow control. As such, the TCA constraint language provides (almost) no other program-flow control mechanism. Procedural languages, on the other hand, have to provide a large number of them. For example, goto, while, if-then-else, and the implicit left-to-right, top-to-bottom program-flow.

TCA constraints are (mostly) bidirectional. Because the TCA constraint language uses relations to implement most functions and operators, one can use the same function [operator] to map a set of arguments to a result, or to map a result back to a set of arguments. Thus, for example, $X = 5! \Rightarrow X : 120$. Further, $120 = N! \Rightarrow N : 5$. In procedural languages, one has to explicitly apply the reverse function to achieve the effect illustrated above. For example, in C programming language, $X = \text{factorial}(5); \Rightarrow X = 120$; and $Y = \text{reverse_factorial}(120); \Rightarrow Y = 5$.

TCA constraint language has no value-storage and no assignment.

With these fundamental differences between the logical and procedural paradigms, the techniques to achieve solutions are also different. In the following section, we describe some of the techniques to write the constraints and to solve them in TCA.

SOME TECHNIQUES TO SOLVE CONSTRAINTS IN TCA

1. Variable Type Specification.

It helps if you can identify the type of the variable explicitly, particularly if it is not real (e.g. integer).

Examples of such type-specification follow:

square(R) = 100, int(R).

5 X=Y^3, X=8, int(Y).

X=Y^3, X=8, real(Y).

2. Range specification.

One can specify boundary conditions for a variable using any of the relational operators (e.g. >, >=, <, <=) available. One

10 can also specify the boundary using the range or the discrete set notation. Some examples of boundary specification follow:

X= 2, [4< Y< 5*X], Z=Y+3.

[2^2 <= X<= 2^4], Y= X*2.

3. Enumerated-Range Specification.

15 One can specify an enumerated range for a variable using the enumerated range construct. Some examples of enumerated-range specification follow:

X= 2, [4< Y< 5*X step 0.5], Z=Y+3.

[2^2 <= X<= 2^4 step 0.3], Y= X*2.

20 4. Efficient Solving.

For performance reasons, it is desirable to use only the constants in the enumerated range specifications of the

independent variables, and impose any other constraints later in the constraint. Thus, for example, the following constraint:

```
int(X,Y,Z), [1<=X<= 100 step 1], [1<=Y<=100
step 1], [gcd(X,Y)<=Z<=100 step 1];
```

5 can be solved more efficiently as:

```
int(X,Y,Z), [1<=X<= 100 step 1], [1<=Y<=100
step 1], [1<=Z<=100 step 1], Z>= gcd(X,Y).
```

5. Representing lists and tables.

One can use (multilayered i.e. lists containing lists) lists
10 to represent tables. For example, a 2x3 table (i.e. a table with
2 rows and 3 columns) can be represented as a 2-element list of
3-element lists e.g. Table_2_3= [[1, 5, 7], [10, 50, 70]]. One
can access the various table-elements using the (potentially,
multi-indexed) list-element-access notation: ListName [Index1 [,
15 Index2 [, Index3 ...]]]. Note that the first element of the
list is indexed 1, second element is indexed 2, and so on.
Multiple indices are used for multilayered lists.

Some constraints involving tables and table-elements and
their solutions are shown below:

```
20 Tbl_4_1= [1, 3, 5, 7], X= Tbl_4_1[2].      =>   X: 3.
Tbl_3_2=[[1,3],[5,7],[9,11]], X=Tbl_3_2[2].  =>   X: [5, 7].
Tbl_3_2=[[1,3],[5,7],[9,11]],X=Tbl_3_2[2,1]. =>   X: 5.
Tbl_3_2=[[a,b],[c,d],[e,f]], X=Tbl_3_2[2,2]. =>   X: d.
```

6. Bidirectionality of functions and operators.

Since the operators and (a large number of) functions in TCA are implemented using relations, one can use the same operators and the functions to map forward and backward and a mixture of forward-and-backward mappings. For example, $X = 4! + 5. \Rightarrow X: 29$. On the other hand, $29 = N! + C, C > 0. \Rightarrow (N: 4, C: 5; N: 3, C: 23; N: 2, C: 27; N: 1, C: 28; N: 0, C: 28)$. Similarly, $29 = N! + 5. \Rightarrow N: 4$.

7. Constraints are Solved in Order-independent Fashion.

Because the constraints are solved as a whole, solutions to the constraints in TCA are (mostly) independent of the constraint-order. Thus, the constraints: $Y = X^2, Y = 2 * Z, Z = 2$. and $Z = 2, Y = 2 * Z, Y = X^2$. provide exactly the same set of solutions: $(X: 2, Y: 4, Z: 2; X: -2, Y: 4, Z: 2)$.

As a practical matter, though, since the constraints are solved left-to-right by the constraint-solver, it often helps to write the constraints in an order such that the more determined constraints are to the left of the less determined constraints.

8. Constraints are Solved as a Whole.

All the constraints specified for one constraint are all solved as a whole, and not partially. This is particularly important in the case of the TCA where constraints are entered on different lines without any explicit operators (e.g. comma or

semicolon) combining them (TCA supplies the default comma-operator (i.e. conjunct) between adjacent constraints) and thus one might get the incorrect impression that the constraints are solved independently.

5 9. Variable Names are the Links to Bind Various Constraints.

One binds various constraints through the variables used in them. Thus, use of the same variable X in constraints C1 and C2 (when C1 and C2 are joined together by the and (i.e. comma) operator) is a statement to solve the constraints C1 and C2 to find the common value for X. For example, $5*5 = X*X + Y*Y$, $\text{int}(X, Y)$, $X = \text{cubert}(27)$. $\Rightarrow \{X: 3, Y: 4\}$. solves the constraints $5*5 = X*X + Y*Y$, $\text{int}(X, Y)$ and $X = \text{cubert}(27)$ to provide the common solution: $\{X: 3, Y: 4\}$, and discards the other solution: $\{X: 4, Y: 3\}$ for the first constraint.

As a corollary, using the same variable-name in multiple constraints forces them to find a common solution. That is, you may unintentionally restrict a solution space by unintentionally using the same variable name across multiple constraints.

20 10. Use of Sets and Ranges.

One can use sets and ranges to solve constraints over continuous ranges or discrete sets. For example, $[1 \leq X \leq 10 \text{ step } 1]$, $Y = X*X$, $\text{int}(X, Y)$. returns (in Y) squares of integers

from 1 through 10. Similarly, X in [-2, -4, 2, 4], Y= X*X*X.
returns (in Y) the cubes of numbers from the given set. Sets and
ranges can often be used in situations which might require
loop-operators in procedural languages.

5 11. Logical Operators.

One can use conjuncts (the comma operator: ,), disjuncts
(the semicolon operator: ;), negation (NOT), and their
combination (using parentheses) to provide any needed
program-flow control.

10 12. Equality by Assigning Same Variable Name.

One can impose equality constraint on variables by
explicitly equating them or by just naming them as the same
variable. By corollary, variables with the same name must have
identical value. Thus, for example, [Div1, Mod1]= divmod(16, 3),
15 [Div2, Mod2]= divmod(17, 3), Div1= Div2. => (Div1: 5, Div2: 5,
Mod1: 1, Mod2: 2). We can impose the same constraint with more
clarity and brevity as: [Div, _] = divmod(16, 3), [Div, _]=
divmod(16, 3). => (Div: 5).

20 Further descriptions of preferred embodiments of the present
invention appears in the Figures and both Source Code Appendices,
all of which are hereby incorporated herein in full.

VISUAL BASIC SOURCE CODE APPENDIX

TABLE OF CONTENTS¹

5	TCA.vbp	VBSCA -1-
	AXProlog.vbp	VBSCA -4-
	Common.bas	VBSCA -5-
10	Main.bas	VBSCA -6-
	modUtil.bas	VBSCA -7-
15	MTAPI.BAS	VBSCA -12-
	MTDeclaration.bas	VBSCA -17-
	MTUtil.bas	VBSCA -21-
20	Timer.bas	VBSCA -28-
	Contraint.frm	VBSCA -29-
25	EditConstraint.frm	VBSCA -50-
	Form1.frm	VBSCA -52-
	frmAbout.frm	VBSCA -54-
30	frmAttributes.frm	VBSCA -55-
	frmComments.frm	VBSCA -60-
	frmDifficulty.frm	VBSCA -62-
35	frmDrag.frm	VBSCA -76-
	frmIED.frm	VBSCA -79-
40	frmIndexedString.frm	VBSCA -81-

¹ All software COPYRIGHT 1999 ETS except for MTAPI.BAS

	frmNew.frm	VBSCA -89-
	frmNewModel.frm	VBSCA -94-
5	frmProgram.frm	VBSCA -97-
	frmProgress.frm	VBSCA -100-
10	frmProlog.frm	VBSCA -102-
	frmSplash.frm	VBSCA -104-
	SetPrecision.frm	VBSCA -108-
15	String.frm	VBSCA -111-
	TCA.FRM	VBSCA -114-
20	Variable.frm	VBSCA -217-
	Application.cls	VBSCA -254-
	CClones.cls	VBSCA -255-
25	CConstraints.cls	VBSCA -261-
	Checksum.cls	VBSCA -268-
30	Clone.cls	VBSCA -270-
	CModels.cls	VBSCA -279-
	Constraint.cls	VBSCA -283-
35	ConstraintSolver.cls	VBSCA -288-
	CVariables.cls	VBSCA -297-
40	CVariants.cls	VBSCA -308-
	DifficultyEstimate.cls	VBSCA -311-
	DocStatus.cls	VBSCA -313-
45	DSMODEL.CLS	VBSCA -314-

	Family.cls	VBSCA -322-
	File.cls	VBSCA -328-
5	FileFind.cls	VBSCA -333-
	GMATDifficultyEstimate.cls	VBSCA -336-
	GREDifficultyEstimate.cls	VBSCA -340-
10	IniFile.cls	VBSCA -345-
	LockedItem.cls	VBSCA -350-
15	Model.cls	VBSCA -362-
	PrintModel.cls	VBSCA -381-
	Progress.cls	VBSCA -384-
20	Prolog.cls	VBSCA -386-
	PSMODEL.cls	VBSCA -392-
25	QCModel.cls	VBSCA -403-
	StringSolver.cls	VBSCA -410-
	StringSolverx.cls	VBSCA -412-
30	SubString.cls	VBSCA -413-
	Value.cls	VBSCA -417-
35	VarFraction.cls	VBSCA -419-
	Variable.cls	VBSCA -428-
	VarInteger.cls	VBSCA -432-
40	VarReal.cls	VBSCA -439-
	VarString.cls	VBSCA -449-
45	VarUntyped.cls	VBSCA -456-

Win32API.cls VBSCA -462-
Word.cls VBSCA -466-

111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

PROLOG SOURCE CODE APPENDIX
TABLE OF CONTENTS²

5	HLP4lib.p4	PROLOG SCA -1-
	PrlgExpr.l	PROLOG SCA -13-
	PrlgExpr.y	PROLOG SCA -16-
10	hlp4API.h	PROLOG SCA -90-

15

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

² All software COPYRIGHT 1999 ETS